

MFP PERFORMANCE ANYWHERE YOU NEED IT

POWERFUL PERFORMANCE IN A COMPACT HYBRID DESIGN

Sharp combines the SIMPLICITY AND CONVENIENCE of network printers with the MULTI-TASKING PRODUCTIVITY of color MFPs to achieve the best of both worlds. The MX-C312 is an exciting example of the SHARP® FRONTIER SERIES, bringing brilliant color output closer to your workgroup with a HYBRID DESIGN that has a small footprint to fit into environments others won't, yet big on functionality. The LARGE 7" DIAGONAL COLOR TOUCH-SCREEN simplifies operation by providing an intuitive user interface to keep ahead of today's fast-paced office document distribution needs. Incorporating next-generation COMMON CONTROLLER ARCHITECTURE, the Frontier Series provides uniform functionality and operability as found in Sharp's AWARD-WINNING MFP PRODUCT LINE. Engineered to help reduce operating costs and downtime, the MX-C312 is easier than ever to set up, monitor and maintain. This model offers modular expandability, remote-access capabilities and a VALUE-ADDED APPROACH to network and software integration. The latest in a long line of innovative products from today's fastest-growing name in office electronics, it also incorporates Sharp's AWARD-WINNING Sharp OSA® PLATFORM and the industry-leading Sharp security suite to help protect data and control access.

innovative

- Vivid color and crisp black-and-white documents can be quickly and accurately produced at speeds up to **31** pages per minute.
- Powerful 800 MHz controller for **true multi-tasking** performance and increased multi-function productivity.
- Large **7" diagonal high resolution, wide-screen color touch display** with an intuitive graphical user interface that makes advanced copying, printing, scanning and faxing functions easy to use.
- Sharp's easy to use Document Filing System provides up to 38 GB of hard drive space for **fast document storage and retrieval**, with **thumbnail view and image preview modes** that allow users to easily locate, identify and retrieve files.
- **Optional Inner Finisher** can be added without taking up much additional space. The space-efficient finisher not only provides exceptional productivity but also automates time-consuming tasks such as stapling, sorting and offset stacking.
- **Direct USB Scanning and Printing** provides a whole new level of convenience. It comes in handy for scanning documents directly to a USB memory device and is an easy way to print PDF documents.
- Sharp's powerful **ImageSEND™** technology securely scans documents to up to seven destinations, including: USB devices, network folders, e-mail, fax machines and desktop PCs, at speeds up to 35 images per minute. You get one-touch distribution features that centralize document workflow helping save time and money.
- The **Remote Front Panel** feature allows administrators and help desk professionals access and control the device from a remote PC workstation. This feature can also be used to help facilitate key operator training.
- The optional **Super G3 Fax Kit** with intelligent Inbound Fax Routing delivers lightning-fast faxing for busy workgroups.
- The optional **Business Card Feeder** can automatically feed and scan business cards and is capable of working with commercially available business card scanning software to automate contact database entry.
- Third-generation Sharp OSA development platform enables users to **access network applications** directly from the device's touch-panel display, helping to **reduce redundancy and streamline workflow**.



MX-C312 SPECIFICATIONS

Main Specifications

| | |
|----------------------|---|
| MX-C312 | Includes multi-tasking controller, 80 GB HDD with document filing system, PCL [®] 5c/PCL6/PostScript [®] 3 network printing, network scanning, 50-sheet RSPF, auto-duplex, 500-sheet paper drawers and 100-sheet bypass. Black and color developer is included in the box. |
| Type | Color multi-function digital document system |
| Functions | Copy, print, network print, network scan, document filing and fax ¹ |
| Copy System | Dry electrostatic transfer/Dual component developer/Magnetic brush development/OPC drums/Heat Roller fusing/Xenon Lamp Exposure |
| Originals | Sheets and Bound Documents |
| Max Original Size | 8-1/2" x 14" |
| Copy Size | Min 5-1/2" x 8-1/2"/Max 8-1/2" x 14" |
| Copy Speed | 31 ppm B&W/Color (Letter) |
| Multiple Copy | Max: 999 copies |
| First Copy Time | Platen glass: 8.0 sec or less (B&W); 8.9 sec or less (color) RSPF: 9.9 sec or less (B&W); 11.5 sec or less (color)* |
| Warm-Up Time | 90 seconds or less* |
| Magnification | 50% to 200% in 1% increments (50 to 200% for RSPF) |
| Original Feed | 50-sheet RSPF with original size detection |
| Scan Speed | Copy mode (Simplex): Up to 35 ipm (B&W or color) @ 600 X 300 dpi. Network Scan (Simplex): Up to 35 ipm (B&W or color) @ 200 x 200 dpi. |
| Original Sizes | 5-1/2 x 8-1/2 / 8-1/2 x 14 (15-lb bond to 110-lb index) |
| Paper Feed System | Standard: 500 sheet paper drawer (Letter/Legal) and 100-sheet bypass tray (Letter/Legal). Optional: Up to 3 additional 500-sheet paper drawers (Letter/Legal) ² |
| Paper Types | Paper drawers: 16-28 lb. bond. Other paper types include: plain, pre-printed, recycled, pre-punched, letterhead, and color paper. Bypass Tray: 16-28 lb. bond (plain paper), 15-16 lb. (thin paper), 28 lb. bond-110 lb. index (heavy paper), 20-24 lb. (Monarch/Com-10 envelope). Other types include label paper, gloss paper, pre-printed, recycled, pre-punched, letterhead, color film and OHP Film. |
| Duplexing | Standard automatic duplex copying and printing |
| CPU | Power QUICCIIII-MPC8533E/800MHz |
| Interface | RJ-45 Ethernet (10Base-T/100Base-TX/1000Base-T), USB 2.0 (Host Port), USB 2.0 (Device Port) |
| Memory | Standard 1 GB (copier); 512 MB (printer/network scanning) memory |
| Hard Disk Drive | 80 GB; up to 50 GB document filing system |
| Copy Resolution | Scan: B&W/Color: 600 dpi; Copy output: B&W/Color 600 dpi |
| Color Modes | Auto Color Control, Full Color Mode, Monochrome (B&W), 2 Color Mode, Single Color Mode. |
| Exposure Control | Modes: Automatic (Color: Magical View, B&W: Character AE) Text, Text/Photo, Text/Printed-Photo, Printed-Photo, Photo, Map, Pale-Color document. Settings: Auto exposure control or 9 step manual exposure. |
| Halftone | 256 gradations/2 levels (monochrome) |
| Copy Features | Scan-Once-Print-Many, electronic sorting, Auto Color Sensing (ACS), Auto Paper Sensing (APS), Auto Magnification Sensing (AMS), Auto tray switching (ATS), rotation copy, reverse copy, margin shift, edge erase, OHP insertion, card shot, reverse image, black-white reversal, centering, proof copy, 2-in-1, photo repeat, document filing, job programs, date/character/page stamp (color) |
| Account Control | Up to 1000 users. Supports user-number authentication (on device), login name/management, date/character/page stamp (color), Copy, Print, Scan, Fax and Document Management |
| Output Tray Capacity | Main output tray (top) 250 sheets (face down) |
| Firmware Management | Flash ROM with local (USB); network update capability and firmware update 1 to N with PAU (Printer Administration Utility) |
| Configuration Method | Web-based management system with user/administrator level login security, cloning (1 to N) with PAU and remote front panel access |
| Service/Maintenance | Remote Front Panel Access to service logs and click counts |
| Power | AC 100-127VAC, 60HZ, 12 AMPS |
| Power Consumption | Maximum: 1.44kW or less. |
| Weight | Approx. 102 lbs (base model) |
| Dimensions | 22-3/64" x 17-1/4" x 28-7/64" |

Network Printing System (Standard)

| | |
|--------------------|--|
| PDL | PCL5c, PCL6, PostScript 3 compatible, optional XPS |
| Resolution | 1200 dpi, 600 dpi |
| Print Speed | 31 pages per minute (Letter) |
| Print Drivers | Windows Server [®] 2003-2008, Windows XP, Windows XP x 64, Windows Server x64, Windows Vista [®] , Windows Vista x 64, Windows [®] 7, MAC [®] OSX [®] (including 10.4.11, 10.5-10.5.8, 10.6-10.6.8, 10.7.2-10.7.4, all MAC PPD). |
| Features | Continuous printing, duplex printing, pamphlet printing, N-up printing, image rotation, different cover page/last page, transparency inserts, carbon copy print mode, fit-to-page, poster print, margin shift, mirror image, watermarks, overlay, confidential print, confidential batch print, print hold, bypass printing, job priority printing and direct printing. (Note: Some features not available on certain print drivers) |
| Direct Printing | File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, PostScript and XPS ¹ . Methods: FTP, WebPage, E-mail and USB Memory |
| Resident Fonts | 80 Outline Fonts |
| Interface | RJ-45 Ethernet 10Base-T/100Base-TX/1000Base- |
| Operating Systems | Windows Server [®] 2003-2008, Windows [®] 2000/XP, Windows Vista, Windows 7, MAC OSX 10.4.11, 10.5-10.5.8, 10.6-10.6.5, 10.6.8, 10.7.2-10.7.4, Novell [®] Netware [®] 3x, 4x, 5x, Sun [®] OS 4.1x, Solaris [®] 2x, Unix [®] , Linux [®] and Citrix [®] (Metaframe, Presentation Server 4, 4.5) and Windows Terminal Services. |
| Network Protocols | TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, 802.1x for Windows and Unix. LPD and LPR for UNIX. IPX/SPX [®] for Novell environments. EtherTalk [®] and NetBEUI, AppleTalk for Macintosh [®] environments. |
| Printing Protocols | LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP and Novell Pserver/Rprinter |
| Network Security | IP/Mac address filtering, protocol filtering, port management, user authentication and document administration. |
| Security Standards | IEEE 2600-2008, DoD (NSTISSP) #11, DoD Directive 8500.2, DoD (DISA) |

Network Scanning System (Standard)

| | |
|------------------------|---|
| Max Original Size | 8-1/2" x 14" |
| Optical Resolution | 600 dpi |
| Output Modes | 600 dpi, 400 dpi, 300 dpi, 200 dpi, 100 dpi |
| Scan Modes | Color, monochrome, grayscale |
| Image Formats | Monochrome: TIFF, PDF, Encrypted PDF, XPS ¹ Color: Grayscale, Color TIFF, JPEG, PDF, Encrypted PDF, XPS ¹ Internet Fax: TIFF-FX, FIFF-F, TIFF-S ¹ |
| Image Compression | Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR) Color/Grayscale: JPEG (High, middle, low) Internet Fax mode: MH/MMR (option) |
| Scan Destinations | E-mail, Desktop, FTP, Folder (SMB), USB, Internet fax (option), Super G3 fax (option) |
| One-Touch Destinations | Up to 999 (combined scan destinations) |
| Group Destinations | Up to 500 |
| Programs | 48 (combined) |
| Max. Jobs in Memory | Up to 94 |
| Network Protocols | TCP/IP and SSL (Includes HTTP, SMTP, LDAP, FTP, POP3), SMB, ESMTP and 802.1x |
| Network Security | E-mail server user authentication for LDAP and Active Directory |
| Software | Sharpdesk [®] desktop document management software (1 user license) |

B&W Super G3 Fax Kit (Option)

| | |
|-------------------------|---|
| Transmission Mode | Super G3, G3 |
| Modem Speed | 33.6 KBPS ³ |
| Compression Methods | JBIG, MMR, MR, MH |
| Scanning Method | Sheet fed simplex or duplex or book |
| Max Transmit Resolution | 400 dpi |
| Transmit Speed | Approximately 2 seconds with Super G3/JBIG ⁴ |
| Auto Dialing | Up to 999 (combined scan destinations) |
| Group Dial/Destinations | Up to 500 |
| Inbound Fax Routing | Forwards received fax data to E-mail, FTP, Desktop, SMB |

B&W Super G3 Fax Kit - Continued

| | |
|-------------|---|
| Long Length | Up to 19.5" (for transmission) |
| Originals | |
| Programs | 48 (combined) |
| Memory | 8 MB (Exclusive) |
| Halftone | 256 levels |
| Features | Quick on-line transmission, direct transmission, F-Code transmission/reception, rotate transmission, anti-junk fax reception, automatically staple received faxes, secure fax release, out of paper memory reception, auto redial, duplex reception transaction reports, activity reports and PC Fax. |

Inner Finisher (Option)

| | |
|------------------------------------|--|
| Type | Built in Finisher |
| Output Capacity | Up to 280 sheets (Letter/Legal), 100 postcard, 20 envelope |
| Output Delivery | Face down |
| Stapling Media | Plain/Thin/Heavy/Recycled/Letterhead/Pre-punched/Colored/Preprinted paper |
| Stapling Positions | Single corner position |
| Power Source | Supplied from the main unit |
| Stapling | 30 sheets Letter/legal |
| Stapled Sets | 10 bundles or 300 sheets (letter/legal) |
| Weight | Approx. 19.8 lbs |
| Dimensions (When Tray is expanded) | 18-2/3" (w) x 13-1/16" (d) x 6-3/16" (h) 20-1/2" (w) x 13-1/16" (d) x 6-3/16" (h) |

Optional Equipment

| | |
|--------------|--|
| MX-BTX1 | Business Card Feeder |
| MX-FN12 | Inner Finisher |
| MX-CFABB | Base Plate with locking casters |
| MX-CFABD | Deluxe Cabinet with door and locking casters |
| MX-CSX1 | 500 sheet Paper Feed Unit for Tray 2 |
| MX-CSX2 | 500 sheet Paper Feed Unit for Trays 3 & 4 |
| MX-PUX1 | XPS Expansion Kit (Requires MX-SHP1GBXPS) |
| MX-SHP1GBXPS | Expansion Memory 1 GB (Required for MX-PUX1) |
| AR-PF1 | Bar Code Font Kit |
| MX-FR29U | Commercial Data Security Kit |
| MX-FXX3 | Fax Expansion Kit |
| MX-FWX1 | Internet Fax Expansion Kit |
| MX-AMX1 | Application Integration Module |
| MX-AMX2 | Application Communication Module |
| MX-AMX3 | External Accounting Module |
| MX-USX1 | Sharpdesk 1 License Kit |
| MX-USX5 | Sharpdesk 5 License Kit |
| MX-US10 | Sharpdesk 10 License Kit |
| MX-US50 | Sharpdesk 50 License Kit |
| MX-USAO | Sharpdesk 100 License Kit |

Supplies

| | |
|-----------|----------------------------|
| MX-C40NTB | Black Toner Cartridge |
| MX-C40NTC | Cyan Toner Cartridge |
| MX-C40NTM | Magenta Toner Cartridge |
| MX-C40NTY | Yellow Toner Cartridge |
| MX-C40NVB | Black Developer |
| MX-C40NVC | Cyan Developer |
| MX-C40NVM | Magenta Developer |
| MX-C40NVY | Yellow Developer |
| MX-C40NRB | Black Drum Cartridge |
| MX-C40NRS | Color Drum Cartridge |
| MX-C31HB | Toner Collection Container |
| MX-SCX1 | Staple Cartridge |

* May vary depending on product configuration, machine settings and operating and/or environmental conditions.

¹ Some features require optional equipment

² Paper capacity is based on letter size paper

³ Actual transmission time will vary based on line conditions

⁴ Based on Sharp Standard Test Chart with approximately 700 characters, letter size in standard resolution



SHARP

SHARP ELECTRONICS CORPORATION
Sharp Plaza, Mahwah, NJ 07495-1163
1-800-BE-SHARP • www.sharpsusa.com

Design and specifications subject to change without notice. Sharp, Sharp OSA, Sharpdesk, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Windows, Windows NT, Windows Server and Windows Vista are trademarks or registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.

