





intimus 175 In the Department

Professional Data Shredders – a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.

- Low noise level
- Integrated Auto Reverse Function for easy removal of paper
- Illuminated indicators for stand-by, basket full, door open and paper jam
- Sealed dust-free design with robust wooden cabinet
- Mounted on rollers for flexible use















DLS.

	Shred size	\1\	m		Security level DIN 66 399			Shredding capacity* sheets		ring Throughput** eed sheets/min		Also shreds:						
Model	mm	- 1		Р	F	0	T	Н	E	70 g/m ²	80 g/m ²	m/s	70 g/m ²	80 g/m ²	U	0		
175 SC2	5.8	175	10+	2	_	2	2+	-	-	65-70	55-60	0.12	1,697	1,455	✓	✓	✓	√
175 SC2	3.8	175	10+	2	_	2	2+	_	-	40-45	35-40	0.12	1,091	970	✓	✓	✓	✓
175 CC3	4 x 40	175	10+	4	_	2	3+	-	-	45-50	38-43	0.13	1,111	949	✓	✓	✓	√
175 CC4	1.9 x 15	175	10+	5	2	4	5 ⁺	-	-	25-30	22-26	0.13	606	525	✓	✓	✓	√
⁺only floppy disks / ID cards																		
High Security Shredder (optionally available with automatic oiler)																		
175 CC5	0.8 x 12	175	10+	6	3	-	-	-	-	15-17	13-15	0.15	515	455	-	-	-	_
175 CC6	0.8 x 4.5	175	10+	7*	3	_	_	_	_	8-10	7-9	0.23	465	418	_	_		_

* NSA approved (NSA / CSS EPL 02/01)

Optional Equipment	Packing unit	Art. No.	Shredder oil for CC-models	Packing unit	Art. No.	
PE bags intimus 130 and 175	50 pieces	99952	Bottle at 110 ml	6 bottles	88035	
Catchbasket intimus 175	1 piece	85829	for models with oiler, 2 litres	1 bottle	91869	

^{*} based on 70 g/m2 A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

^{**} theoretical average performance paper/min