

PRODUCT SPECIFICATIONS



Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
 Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory

4.0 GB RAM

Hard Disk Drive

Standard: 250 GB
 Maximum: 1 TB

Mirroring Hard Disk Drive

Optional: 250 GB, 1 TB
 Method: Raid1

Interface Connection

Network
 Standard: 1000Base-T/100Base-TX/10Base-T,
 Wireless LAN (IEEE 802.11 b/g/n)
 Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
 USB 2.0 x1 (Device)
 Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets
 Maximum: 6,350 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet
 Stack Bypass

Optional: Dual 550-sheet Paper Cassettes
 (CASSETTE FEEDING UNIT-AM1),
 2,450-sheet High-Capacity Paper Cassette
 (HIGH CAPACITY CASSETTE FEEDING
 UNIT-A1), 2,700-sheet Paper Deck
 (PAPER DECK UNIT-F1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets
 Maximum: 3,450 Sheets
 (with External Finisher and Copy Tray)

Finishing Capabilities

Standard: Collate, Group
 With Inner
 Finisher: Collate, Group, Offset, Staple, Hole Punch,
 Staple-Free Staple, Staple On Demand

With External
 Finishers: Collate, Group, Offset, Staple, Booklet, Hole
 Punch, Staple-Free Staple, Staple On Demand

Supported Media Types

Paper
 Cassette 1: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond,
 Transparency, Envelope

Paper
 Cassette 2: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond,
 Transparency, Tab, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond, Coated, Transparency, Tab,
 Tracing,¹ Envelope

Supported Media Sizes

Paper
 Cassette 1: Letter, Executive, Statement-R, Envelope
 [No.10 (COM10), DL, ISO-C5], Custom Size
 (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Paper
 Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
 Executive, Statement-R, Envelope [No.10
 (COM10), Monarch, DL, ISO-C5], Custom Size
 (3-7/8" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Warm-up Time

From Power On: Approx. 10 Seconds²
From Sleep Mode: Approx. 10 Seconds³
Quick Startup Mode: Approx. 4 Seconds⁴

Dimensions (W x D x H)

24-3/8" x 29-1/4" x 37-3/8" (620 mm x 742 mm x 950 mm)⁵

Installation Space (W x D)

Basic: Stack Bypass + Cassette Drawers open: 37-1/8" x 46-3/8" (943 mm x 1,176 mm)

Weight

310.9 lb. (141 kg)⁶

Print Specifications

Print Speed (BW and Color)

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

UFR II, PCL[®] 6, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access⁷

Supported File Types

PDF, TIFF, JPEG, EPS,⁸ XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),⁹ Barcode Fonts¹⁰
PS fonts: 136 Roman

Operating System¹¹

UFR II: Windows[®] Server 2008/Windows[®] 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)
PCL: Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016
PS: Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)
PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing

Copy Specifications

Copy Speed (BW and Color)

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

First-Copy-Out Time (Letter)

C5560i III: As fast as 2.9 seconds (BW)/4.5 seconds (Color)
C5550i III: As fast as 3.5 seconds (BW)/5.2 seconds (Color)
C5540i III: As fast as 4.1 seconds (BW)/6.1 seconds (Color)
C5535i III: As fast as 4.9 seconds (BW)/7.4 seconds (Color)

Copy Resolution (dpi)

Reading: 600 x 600
Printing: 1200 x 1200

Multiple Copies

Up to 999 Copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original, Color Balance, Adjust One-Touch Color, Area Designation

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 5" x 5-1/2" to 12" x 17"

Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m²)
CL Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2" (50 mm), Weight: Up to 4.4 lb. (2kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows 7/8.1/10
Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning (BW): 80 ipm (300 dpi)/80 ipm (600 dpi)
Single-sided Scanning (Color): 80 ipm (300 dpi)/60 ipm (600 dpi)
Double-sided Scanning (BW): 160 ipm (300 dpi)/150 ipm (600 dpi)
Double-sided Scanning (Color): 160 ipm (300 dpi)/80 ipm (600 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV
Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), Limited Color, Device Signature, XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint[®], Word)
Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

Fax Specifications

Maximum Number of Connection Lines

4

Modem Speed

Super G3: 33.6 kbps
G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported
Client PC: Windows (Windows 7/8.1/10)
Concurrent Connections (Max.):
SMB: 64
WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)
Approx. 480 GB (With Optional 1 TB HDD)

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online Express,¹² User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control¹³
Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermark, Encrypted PDF, Encrypted Secure Print, Digital Signatures, Adobe LiveCycle® Rights Management ES2.5 Integration
Optional: User Signatures, Document Scan Lock

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F
Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

C5560i III/
C5550i III: 120-127V AC 60 Hz, 11.5 A
C5540i III/
C5535i III: 120-127V AC, 60 Hz, 10 A

Plug (Main Unit)

C5560i III/
C5550i III: NEMA 5-20P
C5540i III/
C5535i III: NEMA 5-15P

Power Consumption

Maximum: Approx. 1,800 W
Standby: Approx. 65.2 W¹⁴
Sleep Mode: Approx. 0.8 W¹⁵
Typical Electricity Consumption (TEC) Rating:
C5560i III: 3.2 kWh
C5550i III: 2.5 kWh
C5540i III: 2.0 kWh
C5535i III: 1.6 kWh

Standards

ENERGY STAR® Certified
Rated EPEAT® Gold¹⁶

Consumables

Toner

GPR-55 Toner¹⁷

Toner Yield (Estimated @ 6% Coverage)

Black: 69,000 Images
Color (C,M,Y):¹⁷ 60,000 Images

Fiery Print Controller Specifications (Optional)

imagePASS-P2 (Embedded)

System

Fiery FS350

Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

PCL6, Adobe PS 3

Memory

4 GB

Hard Disk Drive

500 GB

Processor

Pentium G4400 (3.3 GHz)

Fonts

PS: 138 Adobe PS Fonts
PCL: 113 PCL Fonts

Supported Operating Systems

Windows 7 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 10 (32 and 64 bit)/Windows Server 2012 (64 bit only)/Windows Server 2012 R2 (64 bit only)/Windows Server 2016 R2 (64 bit only)/MAC OS (10.11 or Higher)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB x 3.0 x 2 (Rear x 2), USB x 2.0 x 4 (Rear x 4)

Network Protocols

TCP/IP FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP

Fiery Print Controller Features

Fiery Command Workstation 6, Paper Catalog, Fiery Spot On, Fiery Remote Scan

Fiery Print Controller Options

Fiery Impose, Fiery Compose, Fiery Impose and Compose, Productivity package Web activate (includes Fierd JDF), Fiery Hot Folders, and Virtual Printers

Direct Print

PDF 1.7, EPS, TIFF 6, JDF 1.4/JMF (OP)

VDP

FreeForm v1, 2.1

Dimensions (W x D x H)

11-1/4" x 3-5/8" x 11-5/8" (285 mm x 93 mm x 295 mm)

Paper Supply Options

CASSETTE FEEDING UNIT-AMI

Paper Capacity: 550 Sheets x 2 Cassettes [20 lb. Bond (80 g/m²)]
Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, and Custom Size [3-7/8" x 7-1/8" to 12" x 18" (98.0 x 182.0 to 304.8 x 457.2 mm)]
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Power Source: From the Main Unit
Dimensions (W x D x H): 24-3/8" x 27-5/8" x 9-7/8" (620 mm x 700 mm x 251 mm)
Weight: Approx. 49.6 lb. (22.5 kg)

HIGH-CAPACITY CASSETTE FEEDING UNIT-AI

Paper Capacity: 2,450 sheets [20 lb. Bond (80 g/m²)]
Paper Size: Letter
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Power Source: From the Main Unit
Dimensions (W x D x H): 24-3/8" x 27-5/8" x 9-7/8" (620 mm x 700 mm x 251 mm)
Weight: 66.1 lb. (30 kg)

PAPER DECK UNIT-F1

Paper Capacity: 2,700 Sheets [20 lb. Bond (80 g/m²)]
Paper Size: Letter

Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Power Source: From the Main Unit
Dimensions (W x D x H): 13-1/2" x 24-7/8" x 17-3/8" (344 mm x 630 mm x 440 mm)
Weight: 68.3 lb. (31 kg)

Output Options

INNER 2-WAY TRAY-J1

Number of Trays: 2
Total Output Capacity: Upper Tray: 100 Sheets
Lower Tray: 250 Sheets
Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Paper Size: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")
Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")
Weight: Approx. 1.3 lb (0.6 kg)

INNER FINISHER-HI

Number of Trays: 2
Top Tray Capacity:¹⁸ Letter/Statement/Statement-R/Executive (45 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (45 Sheets)
Lower Tray Capacity:¹⁸ Letter/Statement/Statement-R/Executive (500 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (250 Sheets)
Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m²)
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Cover (52 to 256 g/m²)
Staple Position: Corner, Double
Staple Capacity: Corner Staple and Double Staple
Letter/Executive: 50 Sheets (14 to 24 lb. Bond) 11" x 17"/Legal/Letter-R: 30 Sheets (14 to 24 lb. Bond)
Staple-Free Staple 11"x17"/Letter: 5 Sheets (14 to 17 lb. Bond) 4 Sheets (17.3 to 21.7 lb. Bond) 3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand: 40 Sheets [20 lb. Bond (80 g/m²)]
Power Source: From the Main Unit
Weight: Approx. 19 lb (8.6 kg)

STAPLE FINISHER-Y1 (External)

Number of Trays: 2
Top Tray Capacity:¹⁸ Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)
Lower Tray Capacity:¹⁸ Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)
Paper Weight: Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Staple Position: Corner, Double
Staple Capacity: Corner Staple and Double Staple
Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m²)]
11" x 17"/Legal/30 Sheets [24 lb. Bond (90 g/m²)]
Letter-R:
Staple-Free Staple: 11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond (52 to 64 g/m²)] 4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)] 3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]
Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m²)]
Power Source: From the Main Unit
Dimensions (W x D x H): 25-1/8" x 24-1/2" x 45" (637 mm x 623 mm x 1142 mm)
Weight: Approx. 68.3 lb (31 kg)

BOOKLET FINISHER-Y1 (External)

Number of Trays:	3
Top Tray Capacity: ¹⁸	Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)
Lower Tray Capacity: ¹⁸	Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)

Paper Weight

Top Tray:	14 lb. Bond to 140 lb. Index (52 to 256 g/m ²)
Lower Tray:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m ²)

Staple Position: Corner, Double

Staple Capacity

Corner Staple and Double Staple Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m²)]

Executive: 11" x 17"/Legal/30 Sheets [24 lb. Bond (90 g/m²)]

Letter-R:

Staple-Free Staple

11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond (52 to 64 g/m²)]
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)]
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]

Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m²)]

Booklet-Stitch

Paper Size: 12" x 18", 11" x 17", Legal, Letter-R, Custom Size [7-3/4" x 10-5/8" to 12" x 18" (195 mm x 270 mm to 304.8 mm x 457.2 mm)]

Booklet-Stitch Staple Capacity: 20 Sheets x 10 Sets [22 lb. Bond (81 g/m²)] (including one cover sheet up to 140 lb.) Index (256 g/m²)

Power Source: From the Main Unit/85.6 W

Dimensions (W x D x H): 25-1/8" x 24-1/2" x 45"

Weight: (637 mm x 623 mm x 1142 mm)

Weight: Approx. 125.7 lb (57 kg)

INNER 2/3-HOLE PUNCHER-B1

(Requires the INNER FINISHER-H1)

Acceptable

Punch Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Acceptable Punch Paper Size

Two Holes: 11" x 17", Legal, Letter, Letter-R, Executive

Three Holes: 11" x 17", Letter, Executive

Power Source: From the Main Unit

2/3-HOLE PUNCHER-A1

(Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1)

Acceptable

Punch Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Acceptable Punch Paper Size

Two holes: 11" x 17", Legal, Letter, Letter-R, Executive

Three holes: 11" x 17", Letter, Executive

Power Source: From the Main Unit

Hardware Options

Card Readers

MICARD PLUS PROXIMITY CARD READER

COPY CARD READER-F1

COPY CARD READER ATTACHMENT-B5

Others

CABINET TYPE-N

BUFFER PASS UNIT-L1

COPY TRAY-J2

UTILITY TRAY-B1

PLATEN COVER TYPE W

PRINTER COVER-J1

TAB FEEDING ATTACHMENT-F1

USB KEYBOARD

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B2

iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON

CRITERIA CERTIFICATION¹⁹

Data Security

HDD MIRRORING KIT-J1

2.5"/250 GB HDD-N1

2.5"/1 TB HDD-P1

REMOVABLE HDD KIT-A1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller

imagePASS-P2

REMOVABLE HARD DISK DRIVE KIT-B1

FIERY IMPOSE

FIERY COMPOSE

FIERY IMPOSE AND COMPOSE

System Accessories

COPY CONTROL INTERFACE KIT-A1

CONNECTION KIT-A1 FOR BLUETOOTH LE

NFC KIT-C1

MEAP WEB CONNECTION KIT-V5.3²⁰

Fax Accessories

SUPER G3 FAX BOARD-AS2

SUPER G3 2ND LINE FAX BOARD-AS2

SUPER G3 3RD/4TH LINE FAX BOARD-AS2

REMOTE FAX KIT-A1

IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1

VOICE GUIDANCE KIT-G1

VOICE OPERATION KIT-D1

BRAILLE LABEL KIT-F1

Staples

STAPLE-P1²¹

STAPLE CARTRIDGE-Y1²²

¹ Some types of tracing paper cannot be used.

² Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.

³ Time from exiting Sleep mode to when printing is operational.

⁴ Time from device power-on to when key operation can be performed on the touch screen.

⁵ Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.

⁶ Includes main unit, consumables, and Cassette Feeding Unit-AM1.

⁷ PDF print from Web sites is supported.

⁸ EPS can be printed directly only from the Remote User Interface.

⁹ Requires the optional PCL International Font Set-A1.

¹⁰ Requires the optional Barcode Printer Kit-D1.

¹¹ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹² No charge for this solution; however activation is required.

¹³ Requires Unified Firmware Platform v3.9.

¹⁴ Reference value (measured one unit).

¹⁵ 0.8 W sleep mode not available in all circumstances due to certain settings.

¹⁶ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

¹⁷ GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.

¹⁸ With 20 lb. Bond (80 gsm) paper.

¹⁹ Will launch at a later date.

²⁰ No charge for this option; however it does need to be ordered.

²¹ Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.

²² Used for booklet finishing only. 3 cartridges per case. 2,000 staples per cartridge.



As an ENERGY STAR[®] Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties.

We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



To learn about Canon's many awards, visit usa.canon.com/awards.