





bizhub 458e

Customer benefits



Intuitive operability Operate the bizhub like a smartphone or tablet with fully customised user interface



Security Secure network integration. data encryption,
HDD overwrite, and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity Reliability, high-speed scanning and printing, combined with powerful finishing functions



Accessibility

Seamless operation of your bizhub device and valuable support for easier access and handling to suit users with special needs



Efficient printer fleet management. including automatic consumables delivery, pro-active maintenance and remote setup

Options



OCR text recognition

Barcode fonts LK-106

Unicode fonts LK-107 OCR A and B fonts LK-108

Document converter pack LK-110v2

ThinPrint® client

Serverless pull printing LK-114

Trusted Platform Module activation LK-115v2



3 OTHERS

Double feed detection kit UK-501

Air cleaning unit

Hard disk mirroring HD-524

Security kit SC-508

Working table WT-506

10-Key pad KP-101



1 x Universal tray PC-115 2 x Universal tray

Large capacity tray PC-415

Copier desk DK-510

Large capacity tray Large capacity tray

Banner tray BT-C1e



Fax board FK-514 x2 Wireless LAN Wireless LAN UK-215

Biometric authentication

ID card reader

Mount kit MK-735

USB I/F kit EK-608 USB I/F kit EK-609

Keyboard holder KH-102

5 MEDIA OUTPUT

Job separator Output tray 0T-506

Inner finisher FS-533

Staple finisher FS-536

Relay unit Staple/booklet finisher FS-536SD

Relay unit

Punch kit

Staple finisher FS-537

Relay unit

Staple/booklet finisher FS-537SD Relay unit RU-513

Z-fold unit ZU-609

Post inserter

LEGEND

Mandatory option Option This option can

only be installed with the respective option above it

Finishing functionalities









punching



punching



Duplex



mixplex/

mixmedia







report



fold



Booklet



OR

Offset sorting





printing

Descriptions

bizhub 458e

A3 multifunctional with 45 ppm b/w. Standard Emperon™ print controller with PCL 6, PCL 5, PostScript 3, PDF 1.7, XPS and 00XML support. Paper capacity of 500 + 500 sheets and 150-sheet manual bypass. Media from A6 to SRA3, 1.2 m banner and $52 - 300 \text{ g/m}^2$. 4 GB memory, 250 GB hard disk and Gigabit Ethernet standard.

ENHANCED FEATURES

| PDF/A; PDF encryption; digital signature |
|---|
| Searchable PDF and PPTX |
| Supports native barcode printing |
| Supports native Unicode printing |
| Supports native OCR A and B font printing |
| Generates various file formats incl. DOCX; XLSX and PDF/A |
| |
| Print data compression for reduced network impact |
| |
| Secure and Follow Me printing solution |
| Secure and Follow Me printing solution requiring no server application. |
| , , |
| |

| CONNECTIVITY | |
|---------------------------------|---|
| FK-514 Fax board | Super G3 fax, digital fax functionality |
| SX-BR-4600 Wireless LAN | Wireless LAN to network connector |
| AU-102 Biometric authentication | Finger vein scanner |
| UK-215 Wireless LAN | Wireless LAN and wireless LAN Access Point Mode |
| ID card reader | Various ID card technologies |
| MK-735 Mount kit | Installation kit for ID card reader |
| EK-608 USB I/F kit | USB keyboard connection |
| EK-609 USB I/F kit | USB keyboard connection; Bluetooth |
| KH-102 Keyboard holder | To place USB keyboard |

OTHERS

| 0111=110 | |
|------------------------------------|--|
| UK-501 Double feed detection kit | Multi-feed detector to reduce errors and paper jams |
| CU-102 Air cleaning unit | Improving indoor air quality by reduced emissions |
| WT-506 Working table | Authentication device placement |
| KP-101 10-Key pad | For use instead of touchscreen |
| SC-508 Security kit | Copy Guard function (2 kits required) |
| HD-524 Hard disk mirroring | Back-up HDD |
| | |
| MEDIA INPUT | |
| PC-115 1 x Universal tray | A5-A3, 500 sheets, 52-256 g/m ² |
| PC-215 2 x Universal tray | A5-A3, 2 x 500 sheets, 52-256 g/m ² |
| PC-415 Large capacity tray | A4, 2,500 sheets, 52–256 g/m ² |
| LU-302 Large capacity tray | A4, 3,000 sheets, 52–256 g/m ² |
| LU-207 Large capacity tray | A4-SRA3; 2,500 sheets; 52-256 g/m ² |
| BT-C1e Banner tray | Multipage banner feeding |
| DK-510 Copier desk | Provides storage space for print media and other materials |
| | |
| MEDIA OUTPUT | |
| JS-506 Job separator | Separation of fax output; etc. |
| OT-506 Output tray | Output tray used instead of finisher |
| RU-513 Relay unit | For FS-536/SD or FS-537/SD installation |
| | (Max. 100 sheets output capacity) |
| FS-536 Staple finisher | 50-sheet stapling, 3,200 sheets max. output |
| FS-536SD Staple/booklet finisher | 50-sheets staple finisher, 20-sheets booklet finisher, |
| | 2,200 sheets max. output |
| PK-520 Punch kit for FS-536(SD) | 2/4 hole punching, autoswitching |
| FS-537 Staple finisher | 100 sheets stapling; 3,200 sheets max. output |
| FS-537SD Staple/booklet finisher | 100-sheets staple finisher; 20-sheets booklet finisher; |
| | 2,700 sheets max. output |
| ZU-609 Z-fold unit for FS-537/SD | Z-fold for A3 prints |
| PK-523 Punch kit for FS-537/SD | 2/4 hole punching; autoswitching |
| PI-507 Post inserter for FS-537/SD | Cover insertion; post finishing |
| | |

Technical specifications

SYSTEM SPECIFICATIONS

| Panel size/resolution | 9" / 800 x 480 |
|-------------------------------------|--|
| System memory (standard/max) | 4,096 MB |
| System hard disk | 250 GB (standard) |
| Interface | 10/100/1,000-Base-T Ethernet; USB 2.0; |
| | Wi-Fi 802.11b/g/n (optional) |
| Network protocols | TCP/IP (IPv4 / IPv6); NetBEUI; SMB; LPD; IPP; SNMP; HTTP |
| Automatic document feeder | Up to 300 originals; A6–A3; 35–210 g/m²; Dualscan ADF |
| (standard) | |
| Printable paper size | A6-SRA3; customised paper sizes; |
| | banner paper max. 1,200 x 297 mm |
| Printable paper weight | 52-300 g/m ² |
| Paper input capacity (standard/max) | 1,150 sheets/6,650 sheets |
| Paper tray input (standard) | 1x 500 sheets; A5–A3; 52–256 g/m²; |
| | 1x 500 sheets; A5–SRA3; 52–256 g/m² |
| Paper tray input (optional) | 1x 500 sheets; A5–A3; 52–256 g/m²; |
| | 2x 500 sheets; A5-A3; 52-256 g/m ² ; |
| | 1x 2,500 sheets; A4; 52–256 g/m² |
| Large capacity tray (optional) | 1x 3,000 sheets; A4; 52–256 g/m²; |
| | 1x 2,500 sheets; A4–SRA3; 52–256 g/m² |
| Manual bypass | 150 sheets; A6–SRA3; custom sizes; banner; 60–300 g/m² |
| Automatic duplexing | A6 portrait; A5–SRA3; 52–256 g/m² |
| Finishing modes (optional) | Offset; group; sort; staple; punch; post insertion; half-fold; |
| | letter-fold; booklet; z-fold |
| Output capacity (standard) | Max. 250 sheets |
| Output capacity (optional) | Max. 3,300 sheets |
| Stapling | Max. 100 sheets or 94 sheets + 2 cover sheets (up to 209 g/m²) |
| Stapling output capacity | Max. 1,000 sheets |
| Letter fold | Max. 3 sheets |

| Letter fold capacity | Max. 30 sheets; unlimited (without tray) |
|------------------------------|--|
| Booklet | Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m²) |
| Booklet output capacity | Max. 100 sheets; unlimited (without tray) |
| Copy/print volume (monthly) | Rec. 30,000 pages; Max. 200,000 pages ¹ |
| Toner lifetime | Up to 26,000 pages |
| Imaging unit lifetime | Up to 275,000/600,000 pages (drum/developer) |
| Power consumption | 220-240 V / 50/60 Hz; Less than 2 kW |
| System dimension (W x D x H) | 615 x 755 x 961 mm (without options) |
| System weight | Approx. 96 kg (without options) |
| | |

50-sheet stapling, 500 sheets max. output

2/4 hole punching, autoswitching

JS-602 Job separator for FS-537/SD Separation of fax output; etc.

DDINTED SPECIFICATIONS

FS-533 Inner finisher

PK-519 Punch kit for FS-533

| PRINTER SPECIFICATIONS | |
|---------------------------|--|
| Print resolution | 1,800 x 600 dpi; 1,200 x 1,200 dpi |
| Page description language | PCL 6 (XL 3.0); PCL 5; PostScript 3 (CPSI 3016); XPS |
| Operating System | Windows 7 (32/64); Windows 8/8.1 (32/64); |
| | Windows 10 (32/64); Windows Server 2008 (32/64); |
| | Windows Server 2008 R2; Windows Server 2012; |
| | Windows Server 2012 R2; Windows Server 2016; |
| | Macintosh OS X 10.8 or later; Unix; Linux; Citrix |
| Printer fonts | 80 PCL Latin; 137 PostScript 3 Emulation Latin |
| Print functions | Direct print of PCL, PS, TIFF, XPS, PDF (v1.7), encrypted |
| | PDF files and 00XML (DOCX, XLSX, PPTX); mixmedia and |
| | mixplex; "Easy Set" job programming; overlay; watermark; |
| | copy protection; carbon copy print |
| Mobile printing | AirPrint (iOS); Mopria (Android); Konica Minolta Print Service |
| | (Android); Konica Minolta Mobile Print (iOS/Android/Windows 10 |
| | Mobile); Mobile Authentication and Pairing (iOS/Android) |
| | optional: Google Cloud Print; WiFi Direct |
| | |

SCANNER SPECIFICATIONS

| OUT WHITE IT OF EOU TO WHO IT | |
|-------------------------------|--|
| Scan speed (mono/colour) | Up to 120 ipm in simplex; Up to 240 ipm in duplex |
| Scan resolution | Up to 600 x 600 dpi |
| Scan modes | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan- |
| | to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; |
| | Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; |
| | TWAIN scan |
| File formats | JPEG; TIFF; PDF; compact PDF; encrypted PDF; XPS; |
| | compact XPS; PPTX |
| | optional: searchable PDF; PDF/A 1a and 1b; |
| | searchable DOCX/PPTX/XLSX |
| Scan destinations | 2,100 (single + group); LDAP support |
| Scan functions | Annotation (text/time/date) for PDF; up to 400 job |
| | programs; real-time scan preview |
| | |

COPIER SPECIFICATIONS

| Imaging technology | Laser |
|----------------------|--|
| Toner technology | Simitri® HD polymerised toner/Polymerised toner |
| Copy/print speed A4 | Up to 45 ppm |
| Copy/print speed A3 | Up to 22 ppm |
| Autoduplex speed A4 | Up to 45 ppm |
| 1st copy out time A4 | 4.0 sec. |
| Warm-up time | Approx. 20 sec. ² |
| Copy resolution | 600 x 600 dpi |
| Gradation | 256 gradations |
| Multicopy | 1-9,999 |
| Original format | A5–A3; custom sizes |
| Magnification | 25-400% in 0.1% steps; auto-zooming |
| Copy function | Chapter; cover and page insertion; proof copy |
| | (print and screen); adjustment test print; digital art |
| | functions; job setting memory; poster mode; image |
| | repeat; overlay; stamping; copy protection |
| | |

FAX SPECIFICATIONS

| TAX OF LOFF TOAT TO NO | |
|------------------------|---|
| Fax standard | Super G3 (optional) |
| Fax transmission | Analogue; i-Fax; Colour i-Fax; IP-Fax |
| Fax resolution | Up to 600 x 600 dpi |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 2,100 (single + group) |
| Fax functions | Polling; time shift; PC-Fax; receipt to confidential box; |
| | Receipt to e-mail/FTP/SMB; up to 400 job programs |

USER BOX SPECIFICATIONS

| COLIT DOX OF EOII TO THOU | |
|---------------------------|--|
| Storable documents | Up to 3,000 documents or 10,000 pages |
| Type of user boxes | Public; Personal (with password or authentication); |
| | Group (with authentication) |
| Type of system boxes | Secure print; Encrypted PDF print; Fax receipt; |
| | Fax polling |
| User box functions | Reprint; combination; Download; |
| | Sending (e-mail/FTP/SMB and Fax); Copy box to box |
| SYSTEM FEATURES | |
| Security | IS015408 Common Criteria (in evaluation); IP filtering |
| | and port blocking; SSL2; SSL3 and TLS 1.0/1.1/1.2 |
| | network communication; IPsec support; IEEE 802.1x |
| | support; User authentication; Authentication log; |
| | Secure print; Kerberos; Hard disk overwrite |
| | (8 standard types); Hard disk data encryption (AES |
| | 256); Memory data auto deletion; Confidential fax |
| | receipt; Print user data encryption |
| | optional: Hard disk mirroring; Copy protection (Copy |
| | Guard, Password Copy) |
| Accounting | Up to 1,000 user accounts; Active Directory support |
| | (user name + password + e-mail + smb folder); User |
| | function access definition; Authentication by mobile |
| | device (Android/iOS) |
| | optional: Biometric authentication (finger vein |
| | scanner); ID card authentication (ID card reader) |
| Software | PageScope Net Care Device Manager; PageScope |
| | Data Administrator; PageScope Box Operator; |
| | PageScope Direct Print; Print Status Notifier; Driver |
| | Packaging Utility; Log Management Utility |
| | |

 $^{^{\}rm 1}$ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m² quality.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (6% coverage of A4). The actual life of each consumable will vary depending on usee and other printing registrons protocols. and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
 Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



































² Warm-up time may vary depending on the operating environment and usage