



#### ESSENTIALS SERIES MONOCHROME DOCUMENT SYSTEMS



MX-M564N shown with options.



Color touch-screen display with intuitive menu navigation.

# The new Sharp Essentials Series workgroup document systems deliver full multifunction capability and excellent value.

The MX-M364N, MX-M464N and MX-M564N monochrome document systems offer flexible multitasking workflow features and high quality output at speeds up to 56 pages-per-minute. Designed for busy workgroup environments, these models combine versatile paper handling with robust finishing options in a compact modular design that is also affordable. The new Sharp Essentials Series can help virtually any office accomplish more in less time.

#### **Key Features**

- Standard full multifunction capability out-of-box includes copying, PCL® 6 network printing and color network scanning for today's demanding office environments
- High-capacity tandem paper drawer and productive inner finisher options provide high functionality in a compact footprint
- Heightened security, including 256-bit data encryption, up to seven-times overwrite protection, and a convenient End-of-Lease feature that erases all user data and job history at trade-in time



images-per-minute.



Up to 6,600-sheet paper capacity with available options.



Available compact inner finisher with 50-sheet staple capacity.

## Enhanced multifunctional capability allows you to meet tomorrow's document needs today.

- Available 500 + 2,000-sheet tandem paper drawer expands maximum online paper capacity to 6,600 sheets
- Flexible paper handling system feeds up to 80 lb. cover through the paper trays and up to 110 lb. cover through the bypass tray
- Supports Sharp's enhanced security platform with standard 256-bit data encryption, up to 7 times overwrite protection, and convenient End-of-Lease feature

- Standard 100-sheet reversing single pass
- 7" (diagonally measured) color touch-screen display with intuitive menu navigation
- Supports the Sharp OSA® development platform, enabling businesses to easily integrate with network applications and cloud services
- Network ready PCL® 6 printing system with available PostScript® 3™

- Available full-size, retractable keyboard allows quick and easy data entry
- 600 x 600 dpi printing provides clear, crisp images even on jobs with fine detail
- ImageSEND™ function scans documents to E-mail, network folders, USB devices and more
- Energy efficient design offers low power consumption, fast warm-up and longer life parts and supplies

### MX-M364N/M464N/M564N SPECIFICATIONS

Main Specifications		Network Printing System		1K Saddle Stitch Finisher (option)	
MX-M364N/	Base models include multitasking controller, 100-sheet RSPF,	PDL	Standard PCL® 6, optional PostScript® 3™ compatible and	Туре	Console finisher with dual exit trays (mounts on left side
M464N/M564N	PCL®6 printing system, network scanning, auto duplexing,		optional XPS		of host machine)
	1 x 500-sheet paper drawer and a 100-sheet bypass tray.	Resolution	600 x 600 dpi	Output Trays	Upper tray: Offset stack tray
Туре	Monochrome multi-function digital document system	Print Speed	36/46/56 pages per minute (8½" x 11")2		Lower tray: Book tray for saddle stitch
Display	7" (diagonally measured) color dot matrix touch panel display.	Print Drivers	Windows Server® 2003-2008, 2012, Windows XP, Windows XP	Output Capacity	1,000 sheets (letter/statement size) or 500 sheets
	800 x 480 dots (W-VGA).		x64, Windows Server 2003-2008 x64, 2012 x64, Windows Vista®,		(legal, ledger, letter)
Functions	Copy, print, network print, network scan, document filing and fax1		Windows Vista® x64, Windows 7, Windows 7 x64, Windows 8,	Stapling	Up to 50 sheets (letter/statement size) or 25 sheets
Copy System	Dry electrostatic transfer/Dual component developer/Magnetic		Windows 8 x64, MAC OSX (including 10.4-10.8), all MAC PPD		(legal, ledger or mixed)
	brush development/OPC drums/Belt type fusing/white LED	Features	Auto configuration, bar code font printing, carbon copy	Output Delivery	Face down
	exposure		print, chapter inserts, color adjustment settings, color mode,	Stapling Media	Plain paper, letter/legal/ledger size or mixed
Originals	Sheets and bound documents		confidential print, continuous printing, different cover page/last	Stapling Positions	1 front, 1 rear, or both
Original Sizes	5½" x 8½", 8½" x 11", 8½" x 11" R, 8½" x 14", 11" x 17"		page/other page, document control, document filing, duplex	Saddle Stitch	Center stitch/center folding (2 staples)
Copy Size	Min. 5½" x 8½", Max. 11" x 17" + 12" x 18"		printing, electronic sorting, folding, form overlay, image rotation,	Function	letter/legal/ledger paper sizes
Copy Speed	36/46/56 ppm (8½" x 11")²		image type, job bypass print, job retention, layout print, margin	Saddle Stitch	Up to 10 sets (11-15 sheets per set)/15 sets
Multiple Copy	Max. 999 copies		shift, multiple pamphlet, network tandem print, N-up printing,	Max. Sets	(6-10 sheets per set)/20 sets (1-5 sheets per set)
First Copy Time	MX-M364N MX-M464N MX-M564N		offset stacking, page interleave, pamphlet style, poster print,	Power	Approx. 70 W or less
Seconds <sup>2</sup>	Platen Glass 4.5 3.9 3.7		proof print, print mode, punching, stapling, tab paper print, tab	Consumption	Approx. 70 W of 1000
Warm Up Time	12 seconds <sup>2</sup>		printing, toner save mode, transparency inserts, tray status, user	Hole Punching	Optional three-hole punch unit MX-PNX5B (MX-FN10)
Magnification	25% to 400% in 1% increments (with document feeder		authentication, watermarks, zoom print¹	Weight	Approx. 88 lbs.
wayiiiication	25%-200%)	Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF,	Dimensions	MX-FN10 (with tray extended):
Original Food	,	Direct Filling		Dillicipions	
Original Feed	100-sheet RSPF with original size detection		PostScript and XPS.¹ Methods: Sharpdesk Mobile, FTP, SMB,		Approx. 26" (w) x 25" (d) x 39" (h)
Scan Speed	Copy: Up to 56 IPM <sup>2</sup>	Desident Fente	Web page, E-mail and USB	Inner Finisher (en	liam)
D	Scan: Up to 56 IPM <sup>2</sup>	Resident Fonts	80 outline fonts (PCL), 136 fonts (PS)	Inner Finisher (op	
Paper Capacity	Standard: 600 Sheets/Maximum: 6,600 Sheets	Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0	Туре	Built-in type stacking finisher
Paper Feed	Standard: (1) 500-sheet paper drawer (letter/legal/ledger/	Operating Systems	Windows Server 2003-2012, Windows XP, Windows Vista,	Output Tray	Offset stacking tray
System	statement) and 100-sheet bypass tray (letter/legal/ledger/		Windows 7, Windows 8, MAC OS X10.4, X10.5, X10.6, X10.7,	Output Capacity	500 sheets (letter size, non-stapled)
	statement/envelope). Optional: single, double or triple drawer		X10.8, Novell® Netware® Unix®, Linux® and Citrix® (XenApp 5.0	Stapling	Three position; Up to 50 sheets (letter/statement)
	paper deck (500 sheets each drawer), tandem paper deck		6.0, 6.5) and Windows Terminal Services, SAP device types.1	Power	Approx. 50 W
	(2,500 sheets) letter/legal/ledger/statement.	Network Protocols	TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, SMTP,	Consumption	
Paper Weights	Paper drawers: 16 lb. bond to 80 lb. cover. Other paper types		POP3, LDAP, 802.1x for Windows and Unix. LPD and LPR for	Hole Punching	Optional three-hole punch unit MX-PN11B
and Types	include plain, pre-printed, recycled, pre-punched, letterhead and		Unix. IPX/SPX® for Novell environments. EtherTalk®. AppleTalk®	Weight	Approx. 26.5 lbs.
	color paper. Bypass tray: 16-28 lb. bond (plain paper), 13-16		for Macintosh® environments.1	Dimensions	(MX-FN11): Approx. 20" (w) x 25" (d) x 43" (h)
	lb. bond (thin paper), 80-110 lb. cover (heavy paper), 20-24	Printing Protocols	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP, POP3, HTTP,		
	lb. bond (Monarch/Com-10 envelope), tab paper (letter). Also		and Novell Pserver/Rprinter	Optional Equipme	nt
	label paper, gloss paper, pre-printed, recycled, pre-punched,	Network Security	IP/MAC address filtering, protocol filtering, port management,	MX-DE12	Stand/1 x 500-sheet Paper Drawer
	letterhead, color paper and OHP film.	-	user authentication and document administration 1	MX-DE13	Stand/2 x 500-sheet Paper Drawer
Duplexing	Standard automatic duplex copying and printing	Security Standards	IEEE-2600™-2008, DoD (NSTISSP) #111	MX-DE14	Stand/3 x 500-sheet Paper Drawer
CPU	Up to 800 MHz multi-processor controller			MX-DE20	Stand/500 + 2,000-sheet Tandem Paper Drawer
Interface	RJ-45 Ethernet (10/100/1000Base-T), USB 2.0 (2 host ports,	Network Scanning	System	MX-LT10	Long Paper Feeding Tray
	front and rear), USB 2.0 (1 device port, rear)	Scan Modes	Standard: Color, monochrome, grayscale	MX-36ABD	Rolling Cabinet Base
Memory	Standard 3 GB copy/print (shared)		600 dpi	MX-LC11	Large Capacity Tray
Hard Disk Drive	320 GB	Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 100 dpi	MX-FN17	Inner Finisher
Copy Resolution	Scan: B&W/color: 600 x 600 dpi; Copy Output: 600 x 600 dpi	Image Formats	Monochrome: TIFF, PDF, PDF/A, Encrypted PDF, XPS	MX-PN11B	3 Hole Punch Unit (MX-FN17)
Copy Modes	Monochrome/Grayscale	illago i orillata	Color: Grayscale, Color TIFF, JPEG, PDF, PDF/A, Encrypted PDF,	MX-SCX1	Staple Cartridge (MX-FN17)
Exposure Control	Modes: Automatic, Text, Text/Photo, Text/Printed-Photo,		XPS; Internet Fax: TIFF-FX, TIFF-F, TIFF-S <sup>1</sup>	MX-FN10	1K Saddle Stitch Finisher
Exposure control		Imaga			
	Printed-Photo, Photo, Map, Pale-Color Document.	Image	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR)	MX-RB22	Paper Pass Unit
11-16	Settings: Auto or 9 step manual	Compression	Color/Grayscale: JPEG (high, middle, low)	MY DUVED	(Required for MX-FN10, MX-FN11 and MX-FN18)
Halftone	256 gradations/2 levels (monochrome)	0 D	Internet Fax mode: MH/MMR (option)	MX-PNX5B	3 Hole Punch Unit (MX-FN10)
Copy Features	Scan-Once Print-Many, electronic sorting, offset-stacking, Auto	Scan Destinations	E-mail, Desktop, FTP, Folder (SMB), USB, Internet fax (option),	AR-SC3	Staple Cartridge (MX-FN10/MX-FN18)
	Paper Selection (APS), Auto Magnification Selection (AMS), Auto		Super G3 fax (option)	MX-FN11	4K Stacking Finisher
	Tray Switching (ATS), black-white reversal, book copy, card	One-touch	Up to 1,000 (combined scan destinations)	MX-FN18	4K Saddle Stitch Finisher
	shot, center erase, centering, cover pages, dual page copy,	Destinations		MX-PNX6B	3 Hole Punch Unit (MX-FN11/MX-FN18)
	edge erase, image edit, image preview, insert pages, job build,	Group Destinations		AR-SC2	Staple Cartridge (MX-FN11/MX-FN18)
	job programs, margin shift, mirror image, mixed size original,	Programs	48 (combined)	MX-TR13N	Right-side Exit Tray Unit
	multi-page enlargement, original count, pamphlet style, proof	Max. Jobs	Up to 94	MX-TU12	Center Exit Tray Unit
	copy, reserve copy, rotated copy, stamp, suppress background,	Network Protocols	TCP/IP and SSL (includes HTTP, SMTP, LDAP, FTP, POP3), SMB,	MX-PK11	PostScript3 Expansion Kit
	tab copy, tab-paper insertion, tandem copy, toner save mode,		ESMTP and 802.1x	MX-PUX1	XPS Expansion Kit
	transparency inserts, watermark, 2-in-1 / 4-in-1 multi-shot	Network Security	E-mail server user authentication for LDAP and Active Directory		(Requires MX-SHP2GBXPS)
Account Control	Up to 1,000 users. Supports user-number authentication, login	Software	Sharpdesk® desktop personal document management software	MX-SHP2GBXPS	2 GB Memory Upgrade (Required for MX-PUX1)
	name/password or login name/LDAP password		(1 user license included), Sharpdesk Mobile (download)	MX-KB14N	Retractable Keyboard
Output Tray	Main output tray (top): 400 sheets (face down); optional right			MX-FX11	Fax Expansion Kit
Capacity	side exit tray: 100 sheets (face down)	B&W Super G3 Fax	r Kit (option)	MX-FWX1	Internet Fax Kit
Firmware	Flash ROM with local (USB), network update capability and firmware	Transmission Mode	Super G3, G3	MX-PF10	Bar Code Font Kit
Management	update 1 to N with SRDM (Sharp Remote Device Manager)	Modem Speed	33.6 KBPS <sup>3</sup>	AR-SU1	Stamp Unit
Device Setup	Web-based management/cloning with user/administrator level login	Compression	JBIG, MMR, MR, MH	AR-SV1	Stamp Cartridge (Requires AR-SU1 Stamp Unit)
Service/Functions		Scanning Method	Sheet fed simplex or duplex or book	MX-AMX1	Application Integration Module
	click counts	Max. Resolution	400 dpi	MX-AMX2	Application Communication Module
Accessibility	Adjustment of key touch sound and speed, document feeder	Transmit Speed	Approx. 2 seconds with Super G3/JBIG <sup>4</sup>	MX-AMX3	External Accounting Module
Features	free stop, job programs, remote front panel, universal grip for	Auto Dialing	Up to 1,000 (combined scan destinations)	MX-FR45U	Commercial Data Security Kit
. outuroo	paper trays, and disable screen timeout	Group Dial	Up to 500 destinations	111-00	(Available shortly after launch)
Environmental	International Energy Star Program Ver. 2.0, European RoHS	Inbound Fax	Forwards received fax data to E-mail, FTP, SMB, Desktop, Fax,	DVENDFS	Generic Vendor Interface Kit
Standards	miomadonal Lifetyy olai Flogram ver. 2.0, European nono	Routing	I-Fax <sup>1</sup>	פיוחוויזאר	GOTIONO VEHICUI IIICETIAGE INI
	AC 100 127 VAC 60 H7 12 Ames			Cumpling	
Power Consumption	AC 100-127 VAC, 60 HZ, 12 Amps	Long Originals	Up to 33 1/4" (for transmission)	Supplies	Tonor Cortridge
Power Consumption		Programs	48 (combined)	MX-560NT	Toner Cartridge
Weight	Approx. 145 lbs.	Memory	1 GB	MX-560NV	Developer
Dimensions	Approx. 24 1/4" (w) x 28" (d) x 33 1/4" (h)	Halftone	256 levels	MX-560DR	Drum

<sup>&</sup>lt;sup>1</sup> Some features require optional equipment. See your local dealer.














Design and specifications subject to change without notice. Sharp, Sharp OSA, Sharpdesk, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Windows and Windows Server are trademarks or registered trademarks of Microsoft Corporation. PostScript 3 is a trademark or registered trademark of Adobe Systems Inc. All other trademarks are the property of their respective owners.



<sup>&</sup>lt;sup>2</sup> May vary depending on product configuration, machine settings and operating and/or environmental conditions.

<sup>&</sup>lt;sup>3</sup> Actual transmission time will vary based on line conditions.

<sup>&</sup>lt;sup>4</sup> Based on Sharp Standard Test Chart with approximately 700