



11" x 17" Multifunction Color

Take advantage of technology that scales and flexes as your business needs do. Be more productive and efficient with the RICOH IM C2000/C2500 range of 11" x 17" color devices.

It's time to:

- Print speeds of 20 25 ppm.
- Easy-to-use 10.1" Smart Operation Panel with intuitive menu.
- Mobile connectivity options including NFC, AirPrint® or Mopria.
- Increased uptime and performance with RICOH Intelligent Support.

Access a range of productivity features and upgrades — such as scanning directly to your email or dedicated folders on your network and ensure you have the latest security enhancements and mobile device connectivity options. Our Intelligent Devices are designed to do more as and when your business needs to do more, using technology that's scalable, secure, sustainable and simple.

Get more from your Intelligent Devices:

- Tailor settings to individual users for quick access to apps used most often.
- Work more efficiently with expanded paper tray capacity.
- Automatic firmware upgrades providing maximum security.

RICOH Intelligent Devices remain current and relevant no matter what your workplace requires. This way, you have ready and easy access to new functionality, when needed. Environmentally-friendly low TEC (Typical Electricity Consumption) values deliver reduced energy consumption and cut running costs, while RICOH Intelligent Support features such as Predictive Maintenance mean that device performance is monitored and any fixes resolved swiftly — minimizing the impact on your workplace.

All Intelligent Devices provide:

- Quick access to Web Help Tools via RICOH Intelligent Support.
- A consistent user interface and experience across your Ricoh fleet.
- Easy integration with third party solutions.
- Regular functionality upgrade releases to do more, smarter and faster.

Ready to take a swipe at a faster way to work? Our range of Intelligent Devices come fitted with a 10.1" Smart Operation Panel designed to enhance your productivity, mobility and environmental commitment. Experience a user interface that offers fast and simple navigation with the ability to customize the layout to best suit your needs — even by adding your own company branding. Access device features, move between jobs and tasks quickly and conveniently enable teams to work smarter.





RICOH IM C2000/IM C2500

MAIN SPECIFICATIONS

Paper types

	IM C2000		IM C2500	
GENERAL				
Warm-up time		21 seconds		
First output speed: B/W	5.1 seconds			
First output speed: full color		7.4 seconds		
Continuous output speed	20 ppm		25 ppm	
Memory: standard Memory: maximum		2 GB		
HDD: standard		4 GB 320 GB		
HDD: maximum		320 GB		
ARDF capacity		100 sheets		
Veight	200.6 lbs / 91 kg		200.6 lbs / 91 kg	
Dimensions: W x D x H		587 x 685 x 913 mm,		
Power source		23.1" x 27.0" x 35.9" 120V - 127V 60Hz		
		120V - 127V 00H2		
COPIER (STANDARD)				
Multiple copying	Up to 999 copies			
Resolution Zoom	600 dpi			
	From 25% to 400% in 1% steps			
PRINTER (STANDARD)				
CPU	Intel Apollo Lake 1.3GHz			
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)			
Printer language: option	Genuine Adobe® PostScript® 3™, PDF Direct from Adobe®			
Print resolution	Up to 1,200 x 1,200 dpi			
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B			
Network interface: option	Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)			
Mobile printing capability	Apple AirPrint®, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector			
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012R2, Windows® Server 2016			
Mac OS environments	Macintosh OS X v10.11 or later			
UNIX environments	UNIX Sun [®] Solaris, HP-UX, SCO OpenServer, RedHat [®] Linux Enterprise, IBM [®] AIX			
SAP® environments	SAP® R3®, S/4®			
Other supported environments	IBM iSeries AS/400 using OS/400 Host Print Transform			
SCANNER (STANDARD)				
Scanning speed	80 ipm (simplex)			
Resolution: maximum	Up to 1,200 dpi			
Compression method	TIFF (MH, MR, MMR, JBIG2), Grayscale	, pp. 000+		
File formats	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, en Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF,			
	* Requires optional OCR Unit Type M13	endyption 1 b1, oct		
Scan modes	E-mail, Folder, USB, SD Card			
FACSIMILE (OPTIONAL)				
,	DCTNL DDV			
Circuit	PSTN, PBX 2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory	**************************************		
Fransmission speed		transmission)		
Modem speed: maximum	33.6 Kbps			
Resolution: standard	8 x 3.85 line/mm, 200 x 100 dpi			
Resolution: option	16 x 15.4 line/mm, 400 x 400 dpi			
Compression method	MH, MR, MMR, JBIG			
Scanning speed	68 spm			
Memory: standard	4 MB (320 pages)			
Memory: maximum	60 MB (4,800 pages)			
PAPER HANDLING				
Recommended paper size	Tray 1: 8-1/2" x 11" (A4)			
	Tray 2: 5-1/2" x 8" - 12" x 18" (SRA3, A3 - A6, B4 - B6), Enve	•	(1.40	
Paner innut: standard	Bypass tray: Up to 12" x 18", Envelopes, Custom Sizes [Width	3.5" - 12.6" (90 - 320 mm), Length: 5.8" - 49.6	" (148 - 1260 mm)]	
Paper input: standard	1,200 sheets			
Paper input: maximum	2,300 sheets	_		
Paper output: standard	500 sheets 8.5" x 11" (A4) or smaller; 250 sheets (B4) or large	r		
Paper output: maximum	1,625 sheets Trays: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m²)			
Paper weight	Bypass: 14 - 80 lb. Bond/166 lb. Index (50 - 300 g/m²)			
	Duplex: 14 - 45 lb. Bond/142 lb. Index (52 - 169 g/m²)			
Paner tynes	Plain Recycled Special Colored Letterhead Cardstock Pre-pr	inted Bond Coated Envelope Label OUR Class		

Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP, Gloss

RICOH IM C2000/IM C2500

MAIN SPECIFICATIONS

	IM C2000	IM C2500	
ECOLOGY			
Power consumption: maximum	Less than 1,584 W		
Power consumption operation: B/W	422.5 W	454.7 W	
Power consumption operation: full color	462.3 W	498.5 W	
Power consumption: ready	45.2 W		
Power consumption: sleep	0.54 W		
TEC1	0.24 kWh	0.29 kWh	
ENERGY STAR®	Certified		
EPEAT [®]	Gold Rated* * EPEAT Gold rating is applicable only in the USA.		

OUTPUT TRAYS AND FINISHER OPTIONS

Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb, Bond/166 lb, Index (60 - 300 g/m²) 1 x 550-sheet Paper Tray (PB3270)

2 x 550-sheet Paper Tray (PB3300) Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m²)

Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Booklet Tray: 8.5" x 11" to 12" x 18" (A4 - A3); Paper weight: 14 - 80 lb. 1.000-sheet Booklet Finisher (SR3270)

Bond/166 lb. Index (52 - 300 g/m²); Stack capacity: 1,000 sheets; Staple capacity: 50 sheets; Staple paper size: Normal Staple: 8.5" x11" to 12x18" (A4 - A3);

Saddle Stitch: 8.5" x 11" to 12" x 18" (A4 - A3), Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m²); Staple positions: Top, Bottom, 2 staples, Booklet 250-sheet Internal Finisher (SR3300)

Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²), Stack capacity: 250 sheets, Staple capacity: 5 sheets,

Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3), Staple paper weight: 17 - 21 lb. Bond (64 - 80 g/m²), Staple positions: Top Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²); Stack capacity: 500 sheets; Staple capacity: 50 sheets;

Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m²); Staple positions: Top, Bottom, 2 staples Tray capacity: 250 sheets with 80g/m² paper (A4, LT or smaller), 125 sheets with 80g/m² paper (B4, LG or larger), Paper size: 12.60" x 23.62" or smaller,

Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²)

One-bin Tray (BN3130) Tray capacity: 125 sheets, Paper size: 5.5" x 8.5" to 12" x 18" (A5 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²)

OTHER OPTIONS

Internal Shift Tray (SH3080)

500-sheet Internal Finisher (SR3250)

Fax Option Type M37, G3 Interface Unit Type M37, Memory Unit Type M37, 4GB, Cabinet Type F, Caster Table Type M3, VM CARD Type M37, Punch units (PU3070, PU3080), PostScript3 Unit Type M37, IEEE 802.11a/g/n Interface Unit Type M19, Device Server Option Type M37, File Format Converter Type M19, OCR Unit Type M13, Imageable Area Extension Unit Type M19, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Flacaket Type M3, NFC Card Reader Type M37, Smart Card Reader Built-in Unit Type M37, ESP XG-PCS-15D, External USB Keyboard (No Bracket), FAX Memory Unit Type M19 64MB, Bridge Unit BU 3090, Banner Paper Guide Tray Type

CONSUMABLES

Toner: black 16,500 prints Toner: cyan/magenta/yellow 10,500 prints Consumable yield measuring method based on A4, 5% coverage

1 TEC value is measured based on the ENERGY STAR Ver. 3.0 test method

Some options may not be available at the time of market release.

Specifications are subject to change without notice

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard Exton, PA 19341



1-800-63-RICOH



www.ricoh-usa.com

