White Toner Transfer Printer **9541WDT**



🖉 Any Color, Any Material

Create beautiful, vibrant prints that transfer onto hundreds of different light and dark materials such as cotton, polyester, denim, wood, acrylic, glass, metal, and more!

🛱 Print to Profit

Print 1 or 1000! With the white toner process, you don't need to set a minimum order quantity. You'll be able to accept one-offs to large custom orders and still profit.

No Weeding, No Problem

Crio® white toner transfers are self-weeding. There is no cutting and no weeding to deal with. Increasing production speed, saving both time and money.

Full Color, High Resolution

Easily print full-color, high-resolution designs or photographs with the widest color gamut up to 1200 x 1200 dpi to transfer even the finest of details.

ڬ Low Cost of Ownership

Crio[®] white toner printers require virtually no maintenance other than replacing standard consumables, as needed. Get additional cost savings by printing true black (K) instead of composite black (CMY).

crio

Ø

Expert Support with CrioCare

From instructional how-to videos to free training, Crio® offers unparalleled support to ensure your success. For peace-of-mind, every Crio[®] printer also comes with a 2-year onsite warranty.



Crio[®] **9541WDT**



Specifications

Performance

- **Print Speed:** 8.5" × 11" transfer media-up to 18ppm; 13" ×1 9" transfer media-up to 12ppm¹
- Processor: 1.2 GHz ARM CPU
- HD Color: Combines multilevel LED printhead and microfine toner for sharp detail and rich color depth
- Print Resolution: 1200 × 1200dpi
- Duty Cycle: 300,000 pages

Memory

• Standard: 2GB RAM

Compatibility

- Emulations: PostScript 3
- Operating Systems: Windows 10 or higher, Mac 10.10 or higher

Connectivity

- Network Interface: 10 Base-T/100
- Base-TX/1000 Base-T Ethernet • Network Protocol: TCP/IP, EtherTalk.
- Network Protocol: TCP/IP, Etherial
 Local Port: High speed USB 2.0

Color Features

Color Solutions: Standard Adobe
 PostScript 3 controller includes Trapping,
 ICC-based Color Management,
 Simulations for SWOP, ISO Coated, Japan
 Color; PDF Direct Print; PS Gamma Adjust;
 Color Correct

Warranty

- **Printer:** 2-year onsite, 2nd business day service
- Digital LED Printheads: 5-year limited warranty

crio

Paper Handling

- Media Capacity: Multi-Purpose Tray (MPT)- Up to 300 sheets; Trays 1/2/3- Up to 530 sheets; High-Capacity Feeder-Up to 1,590 sheets
- Paper Sizes: 13" x 19", Tabloid Extra (12" x 18"), tabloid (11" x 17"), legal, letter, A3, A4, A5, A6 and media up to 52"
- Paper Weight: Trays 1/2/3: 52-320 gsm; Multi-purpose tray: 52-360 gsm

Environmental

- Size: 27.5" x 24.6" x 25.2" (699mm x 625mm x 640mm)
- Weight: 244.4 lbs (110.8 kg) including consumable
- Temperature/Humidity: 50°-90° F (10°-32° C)/20%-80% RH; Quality Assured Range: 66°-80° F (17°-27° C)/50-70% RH
- Power Consumption: Active: 1600W max/1100W avg; Standby: avg 40W; Power Save Mode: 30W or less; Sleep mode: 4W or less; Auto Shutoff: 0.4W or less
- Noise Levels: Active: 57 dBA or less; Standby 34 dBA or less; Power Save mode: Inaudible

Supply Info Crio 9541WDT 120V (multilingual)	Part Numbers 45531000
Toner Cartridges: Cyan: 24,000pg	45531002
Magenta: 24,000pg Yellow: 24,000pg	45531001 45531005
Black: 24,000pg White: 10,000pg	45531003 45531004
Image Drum Kits:	
Cyan: 40,000pg Magenta: 40,000pg Yellow: 40,000pg Black: 40,000pg White: 20,000pg	45532002 45532001 45532005 45532003 45532004
Waste Toner Box	
1 approx: 40,000pg	45533003
Fuser 1 approx: 150,000pg	45533001
Transfer Belt 1 approx: 150,000pg	45533002

¹Published performance results based on laboratory testing of lettersize sheets simplex Individual results may vary ²Based on ISO/IEC 19789

⁸On:site 2nd business day service available in the US and Canada only ⁴Available in the US and Canada only ⁵Based on 5th coverage of lettersize sheet simplex ⁶Based on 3 pages per job

Specifications are subject to change without notice

Your Crio products are distributed by: